

LX-RP 2000 TST

NEW



EQUIPMENT

- Quick release plug-in system D12
- Kränzle in-line RP pump
- Soft start and motor protection
- Total-stop system with delayed motor cut-off
- Stepless pressure regulation
- Convenient integrated hose reel
- 30 m high-pressure hose with twist stop screw connection
- Accessory storage
- All-terrain chassis
- Front and rear impact protection

Ord.no.: 616100

TECHNICAL SPECIFICATIONS

Operating pressure	bar MPa	30-165 3-16.5
Water output	l/min l/h	32 1920
Admissible overpressure	bar MPa	185 18.5
Motor speed	U/min	1400
Connection	V ~ Hz A	400 3 50 16.1
Power intake Power output	kW	9.0 7.5
Power supply cable	m	7.5
Plug		CEE 32A
Dimensions L W H	mm	735 580 1020
Weight	kg	114



EQUIPMENT

High-pressure hose	m	30 (DN10)
Trigger gun with safety catch	Model Ord.no.	Starlet 3 12500
Lance with flat-jet nozzle	Nozzle Ord.no.	13 12420-D4013

YOUR DEALER WILL BE HAPPY TO ASSIST YOU!

TECHNICAL HIGHLIGHTS



QUICK RELEASE PLUG-IN SYSTEM
Easy and quick changing of cleaning lances



KRÄNZLE IN-LINE RP PUMP
First-class flushing effect at high operating pressure



COMFORTABLE HOSE REEL
Space-saving storage of the high-back hose with foldable crank



STEPLESS PRESSURE REGULATION
Suitable operating pressure for every cleaning task



ACCESSORY STORAGE
Practical holders for high-pressure spray guns and cleaning lances



PARKING BRAKE
ensures a secure footing



PUMP HEAD MADE OF SPECIAL BRASS
guarantees maximum efficiency and reliability



CERAMIC PLUNGER
Extremely low wear for maximum service life



MADE IN GERMANY
Developed and manufactured in Illertissen—with over 50 years of experience, expertise, and innovative strength

