









THE NEW PRIMUS SERIES*

kraenzle®

MADE IN GERMANY

COMPACT AND POWERFUL

EQUIPMENT

-  Quick release plug-in system D12
-  Kränzle axial pump
-  Integrated hose reel with roll-up and roll-off support
-  20 m High-pressure hose (2-ply)
-  Twist-Stop screw connection
-  Total-stop system with delayed motor cut-off
-  Pressure regulation
-  Roto-Mold-Chassis



MODEL	Primus 1000 TST	Primus 1200 TST
Ord.no.	614150	614160

TECHNICAL SPECIFICATIONS

Operating pressure	bar MPa	30-220 3-22	30-180 3-18
Water output	l/min l/h	16.6 1000	20 1200
Admissible overpressure	bar MPa	250 25	200 20
Motor speed	U/min	1400	1400
Connection	V ~ Hz A	400 3 50 11.4	400 3 50 11.4
Power intake Power output	kW	7.5 5.5	7.5 5.5
Power supply cable	m	7.5 (4x1.5 mm ²)	7.5 (4x1.5 mm ²)
Dimensions L x W x H	mm	640 515 985	640 515 985
Weight	kg	75	75

EQUIPMENT

High-pressure hose 2-ply	m Ord.no.	20 (DN8) 443812	20 (DN8) 443812
Trigger gun with safety catch	Model Ord.no.	Starlet 3 12500	Starlet 3 12500
Stainless steel lance with flat-jet nozzle	Nozzle Ord.no.	● 05 12420-D2505	● 07 12420-D2507

* Available from quarter 1 / 2023

Technical changes and error reserved

www.kraenzle.com   