

COLD WATER – FOUR WHEELS

The **large quadro-Series**



Figures: quadro 1000 TST
incl. hose drum





Water output < 1000 l/h

For more models from the large quadro series, see the next page

			quadro 800 TST		quadro 1000 TS		quadro 1000 TST	
Technical specifications			incl. hose drum		without hose drum		incl. hose drum	
Operating pressure adjustable	bar / MPa		30-250 / 3-25		30-220 / 3-22		30-220 / 3-22	
Max. admissible overpressure	bar / MPa		270 / 27		250 / 25		250 / 25	
Connected load	V / ~ / Hz / A		400 / 3 / 50 / 12		400 / 3 / 50 / 12		400 / 3 / 50 / 12	
Motor speed	Rpm		1400		1400		1400	
Water output	l/min	l/h	13.3	800	16	960	16	960
Power intake / Power output	kW	kW	7.5	5.5	7.5	5.5	7.5	5.5
Volume water tank	l		16		16		16	
Power supply cable	m		7.5		7.5		7.5	
Dimensions L x W x H	mm		770 / 570 / 990		770 / 570 / 990		770 / 570 / 990	
Weight	kg		89		82		89	
Cleaning Agent Intake			●		●		●	
Equipment								
Hose drum			●		—		●	
Steel braided high-pressure hose	m		20		10		20	
Trigger gun with safety catch	Model		Starlet		Starlet		Starlet	
Turbokiller lance	Nozzle size		● 04		—		● 05	
Stainless steel lance with flat jet nozzle	Nozzle size		● D2504		● D2505		● D2505	
			Standard chassis	Stainless steel chassis	Standard chassis	Stainless steel chassis	Standard chassis	Stainless steel chassis
Ord.no.			40423	404230	404211	404219	40421	404210

EXPERT TIP!

STAINLESS STEEL TROLLEY

The large quadro series is also available with a Stainless steel chassis.

- Corrosion protection
- Extremely stable



For detailed technical information, see page 79



Water output > 1000 l/h

For more models from the large quadro series, see the previous page

			quadro 1200 TS		quadro 1200 TST		quadro 1500 TS		quadro 1500 TST	
Technical specifications			without hose drum		incl. hose drum		without hose drum		incl. hose drum	
Operating pressure adjustable	bar / MPa		30-180 / 3-18		30-180 / 3-18		30-140 / 3-14		30-140 / 3-14	
Max. admissible overpressure	bar / MPa		200 / 20		200 / 20		160 / 16		160 / 16	
Connected load	V / ~ / Hz / A		400 / 3 / 50 / 12		400 / 3 / 50 / 12		400 / 3 / 50 / 12		400 / 3 / 50 / 12	
Motor speed	Rpm		1400		1400		1400		1400	
Water output	l/min	l/h	19	1140	19	1140	25	1500	25	1500
Power intake / Power output	kW	kW	7.5	5.5	7.5	5.5	7.5	5.5	7.5	5.5
Volume water tank	l		16		16		16		16	
Power supply cable	m		7.5		7.5		7.5		7.5	
Dimensions L x W x H	mm		770 / 570 / 990		770 / 570 / 990		770 / 570 / 990		770 / 570 / 990	
Weight	kg		82		89		82		89	
Cleaning Agent Intake			●		●		●		●	
Equipment										
Hose drum			—		●		—		●	
Steel braided high-pressure hose	m		10		20		20		20	
Trigger gun with safety catch	Model		Starlet		Starlet		Starlet		Starlet	
Turbokiller lance	Nozzle size		—		● 07		—		● 11	
Stainless steel lance with flat jet nozzle	Nozzle size		● D2507		● D2507		● M2010		● M2011	
			Standard chassis	Stainless steel chassis	Standard chassis	Stainless steel chassis	Standard chassis	Stainless steel chassis	Standard chassis	Stainless steel chassis
Ord.no.			404221	404229	40422	404220	404261	404269	40426	404260



EXPERT TIP!

TURBOKILLER LANCE (optional quadro TS)

Incredibly powerful rotating, concentrated jet with stainless steel tube. To remove stubborn dirt. Standard issue equipment with hose drum version or optionally available for the quadro series without hose drum.

For more on this, see pages 60-67
(Accessory Compatibility)

For detailed technical information, see page 79-80