

LX-RP-Series



CONVENIENT INTEGRATED HOSE REEL
space-saving storage of the high-pressure hose-with foldable crank

ACCESSORY STORAGE
neat storage for high pressure gun and lances

STAINLESS STEEL PROTECTIVE COVER
durable and corrosion resistant

STAINLESS STEEL PRESSURE GAUGE
easy reading of the working pressure

IMPACT PROTECTION
reduces accidental damage to the high-pressure pump

"RP" IN-LINE PUMP
for magnificent cleaning results with maximum water flow

616080 LX-RP 1600 TST

► **ACCESSORIES** | starting on page 64



EQUIPMENT

- Kränzle in-line pump
- Quick release plug-in system D12
- Total-stop system with delayed motor cut-off
- Safety shutdown
- Pressure regulation
- Locking brake
- Direct suction: Suction height 2.5 m



VARIANT - NON-MARKING

NOM conversion kit Ord.no. **42283**

For further information on NON-Marking please refer to page 74

MODEL	LX-RP 1200 TST	LX-RP 1400 TST	LX-RP 1600 TST
Ord.no. TST incl. hose drum	616060	616070	616080

TECHNICAL SPECIFICATIONS

Operating pressure	bar MPa	30-190 3-19	30-170 3-17	30-150 3-15
Water output	l/min l/h	20 1200	23.3 1400	26.7 1600
Admissible overpressure	bar MPa	210 21	190 19	170 17
Motor speed	Rpm	1400	1400	1400
Connection	V ~ Hz A	400 3 50 14.3	400 3 50 14.3	400 3 50 14.3
Power intake Power output	kW	8.0 6.3	8.0 6.3	8.0 6.3
Power supply cable	m	7.5	7.5	7.5
Plug		CEE 32A	CEE 32A	CEE 32A
Dimensions L x W x H	mm	735 580 1020	735 580 1020	735 580 1020
Weight	kg	94	94	94

EQUIPMENT

High-pressure hose	m Ord.no.	20 (DN8) 443812	20 (DN8) 443812	20 (DN8) 443812
Trigger gun with safety catch	Model Ord.no.	Starlet 123272	Starlet 123272	Starlet 123272
Stainless steel lance with flat-jet nozzle	Nozzle Ord.no.	● 065 12420-D40065	● 08 12420-D4008	● 11 12420-D4011

