


# therm-CA-Series



**ACCESSORY STORAGE**  
neat storage for high pressure gun and lances

**REMOVABLE COVERS**  
convenient and easy service access

**CONVENIENT INTEGRATED HOSE REEL (VARIANTE)**  
space-saving storage of the high-pressure hose - with foldable crank

**CONTROL PANEL**  
analogue temperature regulation

**POWERFUL ENTRY MODEL**  
with all important basic functions



# 626210 therm-CA 12/150

► **ACCESSORIES** | starting on page 64



**EQUIPMENT**

- Quick release plug-in system D12
- Total-stop system
- Pressure regulation
- Cleaning Agent Intake
- Locking brake
- Water tank: Volume 3 liters

**EQUIPMENT HOT WATER**

- Flow monitor
- Combustion chamber pre-ventilation
- Fuel tank: 25 liters



MODEL	therm CA 11/130	therm CA 12/150
Ord.no. without hose drum	<b>626000</b>	<b>626200</b>
Ord.no. incl. hose drum	<b>626010</b>	<b>626210</b>

**TECHNICAL SPECIFICATIONS**

Operating pressure	bar   MPa	30-130   3-13	30-150   3-15
Water output	l/min   l/h	11   660	12   720
Admissible overpressure	bar   MPa	145   14.5	165   16.5
Motor speed	Rpm	1400	1400
Connection	V   ~   Hz   A	230   1   50   15	400   3   50   7.2
Power intake   Power output	kW	3.4   2.3	3.8   3.0
Power supply cable	m	5	7.5
Dimensions L x W x H without hose drum		860   580   970	860   580   970
Dimensions L x W x H incl. hose drum	mm	860   580   1220	860   580   1220
Weight without   incl. hose drum	kg	159   164	159   164

**TECHNICAL DATA HOT WATER**

Hot water output	°C	12-80	12-80
Steam level	°C	140	140
Oil consumption at max. heating output	kg/h   l/h	5.1   6.1	5.4   6.4
Heating oil consumption ΔT 45°	kW	3.2   3.8	3.5   4.1
Heating output	kW	55	58

**EQUIPMENT**

High-pressure hose without hose drum	m   Ord.no.	10 (DN8)   44878	10 (DN8)   44878
High-pressure hose incl. hose drum	m   Ord.no.	15 (DN8)   44879	15 (DN8)   44879
Trigger gun with safety catch	Model   Ord.no.	M2000   12492	M2000   12492
Stainless steel lance with flat-jet nozzle	Nozzle   Ord.no.	● 045   12420-D25045	● 045   12420-D25045
Water inlet filter	Ord.no.	13310	13310