

# therm 1017-Series



**ACCESSORY STORAGE**

neat storage for high pressure gun and lances

**CONVENIENT INTEGRATED HOSE REEL (VARIANTE)**

space-saving storage of the high-pressure hose - with foldable crank

**CONTROL PANEL**

analogue temperature regulation

**REMOVABLE COVERS**

convenient and easy service access

**VISUAL FLAME MONITORING AND OVERHEATING PROTECTION**  
(on page 47)



# 632210 therm 1017

► **ACCESSORIES** | starting on page 64



**EQUIPMENT**

- Quick release plug-in system D12
- Total-stop system with delayed motor cut-off
- Safety shutdown
- Pressure regulation
- Cleaning Agent Intake
- Locking brake
- Direct suction: Suction height 2.5 m
- Water tank: Volume 12 liters

**EQUIPMENT HOT WATER**

- Eco mode
- Flow monitor
- Combustion chamber pre-ventilation
- Visual flame monitoring
- Overheating protection (exhaust temperature in excess of 260 °C)
- Burner stops when there is a lack of heating oil
- Fuel tank: 35 liters



MODEL	therm 1017
Ord.no. without hose drum	<b>632200</b>
Ord.no. incl. hose drum	<b>632210</b>

**TECHNICAL SPECIFICATIONS**

Operating pressure	bar   MPa	30-150   3-15
Water output	l/min   l/h	16.7   1000
Admissible overpressure	bar   MPa	170   17
Motor speed	Rpm	1400
Connection	V   ~   Hz   A	400   3   50   8.5
Power intake   Power output	kW	5.5   4.0
Power supply cable	m	7.5
Dimensions L x W x H without hose drum	mm	1050   800   1015
Dimensions L x W x H incl. hose drum	mm	1050   800   1300
Weight without   incl. hose drum	kg	193   198

**TECHNICAL DATA HOT WATER**

Hot water output	°C	12-80
Steam level	°C	140
Oil consumption at max. heating output	kg/h   l/h	6.2   7.4 ► eco: 4.8   6.3
Heating oil consumption ΔT 45°	kW	5.6   6.6
Heating output	kW	68

**EQUIPMENT**

High-pressure hose without hose drum	m   Ord.no.	10 (DN8)   44878
High-pressure hose incl. hose drum	m   Ord.no.	20 (DN8)   44877
Trigger gun with safety catch	Model   Ord.no.	Starlet   123272
Stainless steel lance with flat-jet nozzle	Nozzle   Ord.no.	● 06   12420-D2506